



**20'**  
8' HIGH  
8' 6" HIGH

# Flat 20'

| Construction  | Inside Dimensions                |                                  |                                  |                                 |                                 |                                | Weights               |                     |                       |
|---|----------------------------------|----------------------------------|----------------------------------|---------------------------------|---------------------------------|--------------------------------|-----------------------|---------------------|-----------------------|
|   | Length of floor                  | Length between Corner Posts      | Width of floor                   | Width between stanchions        | Height                          | Height of Bottom               | Max. Gross            | Tare                | Max Payload           |
| <b>8ft high</b>   |                                  |                                  |                                  |                                 |                                 |                                |                       |                     |                       |
| <b>Steelframe with fixed endwalls and softwood floor</b>  | 5,918mm<br>19ft 5                | 5,625mm<br>18ft 5 <sup>3/8</sup> | 2,398mm<br>7ft 10 <sup>3/8</sup> | 2,208mm<br>7ft 2 <sup>7/8</sup> | 2,172mm<br>7ft 1 <sup>1/2</sup> | 265mm<br>10ft <sup>1/2</sup>   | 24,000kg<br>52,910lbs | 2,800kg<br>6,170lbs | 21,200kg<br>46,740lbs |
| <b>8ft 6 high</b>   |                                  |                                  |                                  |                                 |                                 |                                |                       |                     |                       |
| <b>Steelframe with fixed endwalls and softwood floor</b>  | 5,902mm<br>19ft 4 <sup>3/8</sup> | 5,700mm<br>18ft 8 <sup>3/8</sup> | 2,358mm<br>7ft 8 <sup>7/8</sup>  | 2,235mm<br>7ft 4                | 2,276mm<br>7ft 5 <sup>5/8</sup> | 315mm<br>1ft <sup>3/8</sup>    | 24,000kg<br>52,910lbs | 2,720kg<br>6,000lbs | 21,280kg<br>46,910lbs |
|   | 5,980mm<br>19ft 7 <sup>3/8</sup> | 5,698mm<br>18ft 8 <sup>3/8</sup> | 2,230mm<br>7ft 3 <sup>3/4</sup>  | 2,245mm<br>7ft 4 <sup>3/8</sup> | 2,255mm<br>7ft 4 <sup>3/4</sup> | 336mm<br>1ft <sup>11/4</sup>   | 24,000kg<br>52,910lbs | 2,500kg<br>5,510lbs | 21,500kg<br>47,400lbs |
|   | 5,962mm<br>19ft 6 <sup>3/4</sup> | 5,672mm<br>18ft 7 <sup>1/4</sup> | 2,242mm<br>7ft 4 <sup>1/4</sup>  | 2,242mm<br>7ft 4 <sup>1/4</sup> | 2,261mm<br>7ft 5                | 330mm<br>1ft 1                 | 30,000kg<br>66,140lbs | 2,200kg<br>4,850lbs | 27,800kg<br>61,290lbs |
| <b>Steel container with collapsible endwalls and softwood floor</b>                             | 5,956mm<br>19ft 6 <sup>1/2</sup> | 5,658mm<br>18ft 6 <sup>3/4</sup> | 2,418mm<br>7ft 11 <sup>3/8</sup> | 2,181mm<br>7ft 1 <sup>7/8</sup> | 2,320mm<br>7ft 7 <sup>3/8</sup> | 271mm<br>10ft <sup>5/8</sup>   | 33,050kg<br>72,860lbs | 3,045kg<br>6,710lbs | 30,005kg<br>66,150lbs |
| <b>Steel container with collapsible flush folding endwalls – can be converted to a platform</b> | 5,950mm<br>19ft 6 <sup>1/4</sup> | 5,675mm<br>18ft 7 <sup>3/8</sup> | 2,428mm<br>7ft 11 <sup>5/8</sup> | 2,213mm<br>7ft 3 <sup>3/8</sup> | 2,270mm<br>7ft 5 <sup>3/8</sup> | 316mm<br>1ft <sup>3/8</sup>    | 33,000kg<br>72,752lbs | 2,600kg<br>5,732lbs | 30,400kg<br>67,020lbs |
|   | 6,038mm<br>19ft 9 <sup>3/4</sup> | 5,638mm<br>18ft 6                | 2,208mm<br>7ft 2 <sup>7/8</sup>  | 2,438mm<br>8ft                  | 2,235mm<br>7ft 4                | 370mm<br>1ft 2 <sup>9/16</sup> | 30,480kg<br>67,200lbs | 2,520kg<br>5,560lbs | 27,960kg<br>61,640lbs |
|   | 6,038mm<br>19ft 9 <sup>3/4</sup> | 5,612mm<br>18ft 4 <sup>7/8</sup> | 2,210mm<br>7ft 2 <sup>7/8</sup>  | 2,438mm<br>8ft                  | 2,213mm<br>7ft 3 <sup>1/8</sup> | 370mm<br>1ft <sup>9/16</sup>   | 34,000kg<br>74,956lbs | 2,740kg<br>6,040lbs | 31,260kg<br>68,910lbs |